

PLEASE READ BEFORE USING PRODUCT



SC Premium™ Color Laser Copier Transfer Paper

Imprintables™
WAREHOUSE

Recommended Copiers: Cannon 500, 550, 700, 800, Savin CS106, Kodak 1550, 150+, 1565, Ricoh NC 5006, 5106, 5206

Recommended Substrates: Cotton, Polyester, Poly / Cotton Blends, Fleece, Poly / Foam Hats

Items needed: Computer, Graphics Software, Color Laser Copier, SC Premium™ Color Laser Paper, Heat Press

RECOMMENDED APPLICATION FOR SC PREMIUM™ Transfer Paper

1) CREATE DESIGN ~ Using graphics software, create a design and output to your color laser printer. Fan sheets prior to loading. *Be sure to print your design in the REVERSE / MIRROR format.

2) TRIM TRANSFER ~ Trim the excess transfer paper away from the design before heat applying. *Trimming as close as possible will result in a cleaner, more precise finished product.

3) PREHEAT GARMENT ~ It is extremely important to preheat the garment before application. Press garment for **3-5 seconds** to remove moisture and chemical treatment from the transfer area.

4) POSITION DESIGN ~ After preheating the garment, position the design face down onto the garment.

5) HEAT APPLY ~ Heat apply the design for **15 seconds** at **375° F** using **HEAVY** pressure. Peel away the backing immediately.

PEEL HOT !

TIPS :

*Before using, place paper in a zip-close bag with desi-pak and store flat in a cool, dry place for 24 hours. This will remove any moisture built up during shipping. Optimum humidity level of copier area and storage area for papers is 40%.

*Best performance is obtained on Cotton, Polyester and Poly / Cotton.

IMPORTANT: Please keep your SC Premium™ paper in the plastic bag until actual use. This will keep moisture out of the paper. Close the bag after each use.

Great for creating transfers for white, T-shirts, mousepads, caps & more!

Helpful Tip!



**PREHEAT YOUR
GARMENT!**

*** Don't forget to Mirror
Your Designs! ***

***Your Notes:**

Care Instructions

Turn garment inside out & machine wash in warm or cold water ~ mild detergent. Do not bleach.
Tumble dry at a low setting.

Do NOT iron directly over design.

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance under conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

PHONE 1.800.347.0068

www.imprintables.com

FAX 724.583.0426